



MATERIAL SAFETY DATA

EDITION: 7 DATE: DECEMBER 2004

1. PRODUCT

NAME: **weber.tec ritecure** (ritecure 90 clear)

Chemical Nature

A solution of inert hydrocarbon resins in white spirit

Manufacturer

Weber

Saint-Gobain Weber Limited

Dickens House

Enterprise Way

Flitwick

Bedford

MK45 5BY

EMERGENCY TELEPHONE NUMBER. 08703 330070

2. COMPOSITION

Contains white spirit (60-90%) CAS No. 64742-82-1 and inert hydrocarbon resin (1030%)

EEC Symbol: Xn

R Phrases 10, 20, 36/38, 43, 65, 66

3. HAZARDS IDENTIFICATION

Flammable Flash point 36°C.

Harmful by inhalation. Irritating to eyes and skin

May cause sensitisation by skin contact

Harmful; may cause lung damage if swallowed

Repeated exposure may cause skin dryness or cracking

4. FIRST AID MEASURES

SKIN CONTACT:

Immediately Wash with plenty of soap and water

EYE CONTACT:

Rinse immediately with water for at least 15 minutes. Seek medical attention immediately

INHALATION:

Move affected person to fresh air. If recovery not rapid seek medical attention

INGESTION:

Immediately rinse mouth repeatedly with water. If swallowing has occurred do not induce vomiting. Seek medical attention immediately

5. FIRE-FIGHTING MEASURES

Suitable Extinguishers: Carbon dioxide, Foam and Dry powder. Do not use water.

Exposure hazards

Do not release chemically contaminated water into drains, soil or surface water. Sufficient measures must be taken to retain water used for extinguishing. Dispose of contaminated water and soil according to local regulations.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Avoid contact with skin, eyes and clothing.
Avoid breathing dust or vapours.
Avoid ignition sources.

Environmental Precautions

Prevent contamination of soil drains and surface water.

Methods for Cleaning

Take up with absorbent, dry inert material and place in a suitable and closable container for disposal by burning in an approved installation according to local regulations.

7. HANDLING AND STORAGE

Handling

Irritant. Avoid vapour formation and ignition sources. Ensure good ventilation. Do not eat or drink in workplace.

Storage

Store away from food and drink. Store in original undamaged containers securely closed. Store at room temperature away from direct sunlight. Keep away from sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Technical Protective Measures

No special measures required

Exposure Limits

Occupational Exposure Standards 8 hour TWA (According to EH40/00) 600mgm⁻³

Respiratory Protection

Not normally necessary. Work in well ventilated area.
Wear suitable vapour mask if working in confined spaces.

Hand Protection

Wear suitable gloves.

Eye Protection

Wear suitable goggles or face protection

Skin Protection

Wear overalls and closed footwear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: low viscosity liquid. Flash Point: 36°C.

Boiling Point: approx 152 - 198°C

Auto-Ignition Temperature: 230°C

Vapour Pressure: 3.3mmHg@ 20°C

Insoluble in water.

10. STABILITY AND REACTIVITY

Stable under normal room temperature storage conditions avoid sunlight.

11. TOXICOLOGICAL INFORMATION

Skin Irritation: Irritating to skin Eye irritation: Irritating to eyes Inhalation: Harmful by inhalation.

12. ECOLOGICAL INFORMATION

Prevent contamination of soil, drains or surface water.
Slightly toxic to aquatic organisms, but in most cases is unlikely to persist for sufficient time to pose a significant hazard. Can be expected to biodegrade slowly.

13. DISPOSAL CONSIDERATIONS

Incineration in approved installation.
Contaminated packaging material should be disposed of identically to the product itself.

14. TRANSPORT INFORMATION

RID/ADR: Class 3 IMDG-Code: Class 3 IATA: Class 3 UN No.: 1866 Label 070 Marine
Pollutant Flash Point: 36°C

15. REGULATORY INFORMATION

Symbol: Xn
Contains: White spirit (60-90%) CAS No. 64742-82-1 and inert hydrocarbon resin (10-30%)

R Phrases:

R10: Flammable
R20: Harmful by inhalation
R36/38: Irritating to eyes and skin
R43 May cause sensitisation by skin contact
R65 Harmful; may cause lung damage if swallowed
R66 Repeated exposure may cause skin dryness or cracking

S Phrases:

S24 Avoid contact with skin
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical attention.
S28: After contact with skin, wash immediately with plenty of soap and water.
S29/56 Do not empty into drains, dispose of this material and its container to hazardous or special waste collection point
S37/39 Wear suitable gloves and eye/face protection.
S43 In case of fire use foam/dry powder/CO₂ - NEVER USE WATER.
S46 If swallowed seek medical advice immediately and show the container label
S51 Use only in well ventilated areas
S61 Avoid release to the environment. Refer to special instructions/safety data sheet
S62 If swallowed, do not induce vomiting. Seek medical advice immediately

16. OTHER INFORMATION

None

This safety sheet has been prepared in accordance with the provisions of the EC SDS Directive 91/155.