



MATERIAL SAFETY DATA

EDITION: 8 DATE: OCTOBER 2007

1. PRODUCT

NAME: **weber.tec bedding mortar**

Chemical Nature

Two-component pack comprising a can of liquid polyester resin (with characteristic sweet aromatic odour of styrene monomer) and a bag of fine filler/hardener.

Manufacturer

Weber
Saint-Gobain Weber Limited
Dickens House
Enterprise Way
Flitwick
Bedford.
MK45 5BY.

EMERGENCY TELEPHONE NUMBER. 08703 330070

2. COMPOSITION

Resin component: Unsaturated polyester resin in styrene (CAS No; 100-42-5) approx 45% weight.

EEC Symbol: Xn R Phrases: 10,20, 36/38 & 43

Filler/hardener component: fine inert powders containing small quantities of respirable dust and <2% dibenzoylperoxide.

EEC Symbol: None R Phrases: 36, 43 & 7.

3. HAZARDS IDENTIFICATION

Resin component
Flammable.
Harmful by inhalation.
Irritating to eyes and skin
May cause sensitisation by skin contact
Flash Point 31°C.

Filler/Hardener component:
Irritating to eyes.
May cause sensitisation by skin contact.
May cause fire.
Contains dibenzoyl peroxide. May produce an allergic reaction.

4. FIRST AID MEASURES

SKIN CONTACT:	Wipe off excess with absorbent disposable paper towels. Wash with plenty of soap and water. Do not use organic solvents.
EYE CONTACT:	Rinse immediately with water for at least 15 minutes. Seek medical attention immediately.
INHALATION:	Move affected person to fresh air. If recovery not rapid seek medical attention.
INGESTION:	Immediately rinse mouth repeatedly with water. If swallowing has occurred do not induce vomiting. Seek medical attention immediately.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishers: Carbon dioxide, Foam and Dry powder. Do not use water. Fire fighters should wear breathing apparatus.

Exposure hazards

Do not release product into drains, soil or surface water. Sufficient measures must be taken to retain water used for extinguishing. Dispose of contaminated water and soil according to local regulations

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Avoid contact with skin, eyes and clothing. Avoid breathing dust or vapours Avoid ignition sources.

Environmental Precautions

Prevent contamination of soil drains and surface water.

Methods for Cleaning

Take up with absorbent, dry inert material and place in a suitable and closable container for disposal by burning in an approved installation according to local regulations

7. HANDLING AND STORAGE

Handling

Harmful, sensitising. Avoid vapour formation and ignition sources. Avoid raising dust. Ensure good ventilation. Do not eat or drink in workplace.

Storage

Store away from food and drink. Store in original undamaged containers securely closed. Store at room temperature away from direct sunlight. Keep away from sources of ignition. Keep away from oxidizing materials. Keep away from heat

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Technical Protective Measures

No special measures required

Exposure Limits

Workplace Exposure Limits 8 hour TWA (According to EH40/05)

Resin: contains styrene 100ppm (430mg/m³)

Short-term (according to EH40/05) (MEL-TWA) 15 minutes styrene 250ppm (1080mg/m³)

Filler/hardener: Total inhalable dust	10mg/m ³
Respirable dust	4mg/m ³
Diabenzoyl peroxide	5.0mg/m ³

Respiratory Protection

Not normally necessary. Work in well ventilated area. Wear suitable vapour mask if working in confined spaces. Wear dust mask if there is risk of raising dust.

Hand Protection

Wear suitable gloves (solvent-proof).

Eye Protection

Wear suitable goggles or face protection. Contact lenses should not be worn.

Skin Protection

Wear impermeable overalls and closed footwear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Resin Component

The resin is a low viscosity flammable liquid.

Flash Point:	31°C.
Boiling Point:	approx 145°C
Auto-Ignition Temperature:	490°C
Vapour Pressure:	6.52mb (652N/m ²) at 20°C (styrene)

The filler/hardener is a fine powder

10. STABILITY AND REACTIVITY

Stable under normal room temperature storage conditions avoid sunlight. Materials to avoid: Strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

Resin Component

Acute toxicity LD50: An oral LD50 in rats of 5g/Kg has been reported for styrene

LC50: Inhalation in rats 12mg/litre/4hr (styrene).

Skin Irritation: Irritating to skin. May cause sensitisation by skin contact

Eye irritation: Irritating to eyes

Inhalation: Harmful by inhalation. Concentrations above 100ppm may cause impairment of nervous system

12. ECOLOGICAL INFORMATION

Prevent contamination of soil, drains or surface water. Styrene is harmful to aquatic organisms.

No other specific information available

13. DISPOSAL CONSIDERATIONS

Incineration in approved installation.

Contaminated packaging material should be disposed of identically to the product itself.

For easy disposal any unmixed resin and hardener can be mixed and allowed to cure.

Once fully cured Certite Resin Anchor Grouts can be disposed of as normal household waste. Uncontaminated packaging material should be treated as household waste or as recycling material

14. TRANSPORT INFORMATION

RID/ADR: UN No. 1866
Resin solution Class 3
Label 070

IMDG-Code: UN No. 1866
Resin solution Class 3
Label 070
Marine Pollutant P
Packing group 3.

ICAO/IATA: UN No 1866
Resin Solution Class 3
Label 070
Packing group 3

Flash point 31°C

15. REGULATORY INFORMATION

Resin Component:

Symbols: Xn
Contains: Styrene (CAS No: 100-42-5)

R Phrases:

R10: Flammable
R20: Harmful by inhalation
R36/38: Irritating to eyes and skin
R43: May cause sensitisation by skin contact.

S Phrases:

S2: Keep out of reach of children.
S13: Keep away from food, drink and animal feeding stuffs.
S23: Do not breath vapour.
S28: After contact with skin, wash immediately with plenty of soap and water.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical attention.
S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.
S51: Use only in well ventilated areas.

Filler/Hardener Component:

Symbol: None
Contains: <2% dibenzoyl peroxide. May produce an allergic reaction.

R Phrases:

R36: Irritating to eyes.
R43: May cause sensitisation by skin contact.
R7: May cause fire.

S Phrases:

S3/7: Keep container tightly closed in a cool place.
S14: Keep away from reducing agents (eg; amines), acids, alkalis and heavy metal compounds (eg; accelerators, driers, metal soaps).
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.
S50: Do not mix with peroxide-accelerators or reducing agents.

16. OTHER INFORMATION

None

This safety sheet has been prepared in accordance with the provisions of the EC SDS Directive 91/155.