



## MATERIAL SAFETY DATA

EDITION: 4      DATE: AUGUST 2007

### 1. PRODUCT

NAME: **FIVE STAR GROUT STANDARD**

#### Chemical Nature

An odourless grey powder containing granular material insoluble in water

#### Manufacturer

##### **Weber**

Saint-Gobain Weber Limited  
Dickens House  
Enterprise Way  
Flitwick  
Bedford.  
MK45 5BY.

EMERGENCY TELEPHONE NUMBER. 08703 330070

### 2. COMPOSITION

A blend of Portland cement, graded silica sands and with small quantities of other additives.

EEC Symbol: Xi      R Phrases:      36/38

### 3. HAZARDS IDENTIFICATION

Contains chromium VI. May produce an allergic reaction  
When mixed with water or contact of powder with body fluids produces a strongly alkaline solution. This may cause serious burns and ulceration both to the skin and eyes.

This product, until set, may cause dermatitis due to either its high alkalinity or hexavalent chromium salts present in Portland cement.

### 4. FIRST AID MEASURES

SKIN CONTACT:      Wash the affected area thoroughly with soap and water. If irritation continues seek medical advice. Clothing contaminated with wet product should be removed and washed thoroughly before reuse

EYE CONTACT:      Wash eyes immediately with plenty of clean water for at least 15 minutes and seek medical advice without delay

INHALATION:      Move affected person to fresh air. If nose or airways become inflamed seek medical attention

INGESTION: If swallowing has occurred do not induce vomiting. Give person plenty of water to drink. Seek medical attention

## 5. FIRE-FIGHTING MEASURES

This product is not flammable and will not facilitate combustion of other materials

### Exposure hazards

Do not release water contaminated with this product into surface water drains

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions

Avoid contact with skin, eyes and clothing. Avoid breathing dust.

### Environmental Precautions

Prevent contamination of surface water.

### Methods for Cleaning

Recover spillage in dry state if possible. Minimise generation of airborne dust. The product can be slurried with water. Keep children away from clean up operations. Dispose of according to local regulations

## 7. HANDLING AND STORAGE

### Handling

When handling bags of this product due regard should be paid to Manual Handling Operations Regulations.

Some bags may have a small amount of cement dust on their outer surface. Appropriate personal protection should be used whilst handling.

### Storage

Bags should be stacked in a safe and stable manner. Store in dry conditions.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Technical Protective Measures

No special measures required.

### Exposure Limits

Workplace Exposure Limit (OEL) 8 hour TWA (According to EH40/05):

Portland cement:	Total inhalable dust:	10mg/m <sup>3</sup>
	Respirable dust	4mg/m <sup>3</sup>

### Respiratory Protection

Suitable respiratory protection should be worn to ensure that personal WEL is not exceeded. If care is taken not to raise dust during handling the use of respirators is not normally necessary.

### Hand Protection

Wear suitable gloves.

### Eye Protection

Suitable goggles or face protection should be worn wherever there is a risk of product powder or product/water mixture entering the eye.

### Skin Protection

Wear overalls and closed footwear

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state: Particulate  
Particle size: 5 - 2000 microns  
pH: pH of wet cement 12 - 14

## **10. STABILITY AND REACTIVITY**

Stable under normal room temperature storage conditions. Bags will set solid if continually soaked with water

## **11. TOXICOLOGICAL INFORMATION**

### Eye Contact

Cement constituent is severe eye irritant. Mild exposures can cause soreness. Gross exposures or untreated mild exposures can lead to chemical burning and ulceration of the eye.

### Skin Contact

The powder or product/water mixture may cause irritation, contact dermatitis or allergic dermatitis and/or burns.

### Inhalation

Inhalation of the powder may cause inflammation of mucous membranes.

### Ingestion

The swallowing of small amounts of product or product /water mixtures is unlikely to cause any significant reaction. Larger doses may result in irritation to the gastro intestinal tract.

## **12. ECOLOGICAL INFORMATION**

### Aquatic Toxicity Rating

LC50 aquatic toxicity rating not determined. The addition of this product to water may, however, cause the pH to rise and therefore may be toxic to aquatic life in some circumstances.

No other specific information available.

## **13. DISPOSAL CONSIDERATIONS**

Dispose of according to local regulations

## **14. TRANSPORT INFORMATION**

Classification for Transport not required.

## 15. REGULATORY INFORMATION

Symbol: Xi Irritant

Contains: Portland Cement (C.A.S No. 65997-15-1).  
Contains chromium VI. May produce an allergic reaction

### R Phrases:

R36/38: Harmful to eyes and skin

### S Phrases:

S2: Keep out of reach of children

S28: After contact with skin, wash immediately with plenty of soap and water.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical attention.

S37/39: Wear suitable gloves and eye/face protection.

## 16. OTHER INFORMATION

None

This safety sheet has been prepared in accordance with the provisions of the EC SDS Directive 91/155.