

A synthetic, water-based PVA concentrate for sealing and priming building substrates

weber PR370

universal



About this product

weber PR370 is a synthetic, water-based PVA concentrate for sealing and priming building substrates.

Technical data

Relative density	1.05
Solids content	40%
pH	4.5

Application properties

Application temperature	Between +5°C and +35°C
Drying time	1 – 4 hours
Time before coating	1 hour minimum

Uses

As a primer for porous surfaces in interior, dry situations:

- Plaster
- Plasterboard
- Concrete
- Blockwork

Features and benefits

- ▲ Manufactured under BSI Quality Assurance Scheme ISO 9001
- ▲ Seals dusty or porous surfaces prior to tiling
- ▲ Supplied as a concentrate
- ▲ When diluted 5:1, one 2.5 kg bottle will cover approximately 25 m²
- ▲ Can be used neat or diluted (substrate dependent)

weber PR370

Preparation

weber PR370 is recommended when tiling onto porous substrates such as plaster, plasterboard, blockwork, in dry, interior situations.

Ensure that the surface is clean, dry, sound and dust-free.

Ensure that the surface is free from grease or any other contamination.

Mixing

Shake well before use. For priming smooth, dusty/porous surfaces, mix together 1 part of primer with 5 parts of water.

For priming very coarse, open surfaces, mix together 1 part of primer with 3 parts of water.

Application

Do not use at temperatures below 5°C.

Use a brush or sponge to apply the primer mixture. Leave to dry before tiling (this may take 1 to 4 hours, depending on the film thickness and the ambient temperature).

Packaging

weber PR370 is supplied in 2.5 kg plastic bottles.

Coverage

Approximate coverage is 0.1 kg/m² when 1 part primer is diluted with 5 parts water.

Storage and shelf life

When stored airtight in a cool, dry place at temperatures above 5°C and protected from frost, shelf life is 12 months from date of manufacture.

Health and safety

Essentially not hazardous.
Not harmful during normal use.
After contact with skin, wash immediately with plenty of water.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Keep out of the reach of children.

For further information, please request the Material Safety Data Sheet for this product.

Technical services

Weber's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical helpline
Tel: (01525) 722137

Sales enquiries

Weber products are distributed throughout the UK through selected stockists and distributors. For UK sales enquiries and overseas projects, contact **Weber's** Sales office.

Sales office
Tel: (01525) 722100
Fax: (01525) 718988

Saint-Gobain Weber Ltd
Dickens House, Enterprise Way, Maulden Road, Flitwick, Bedford MK45 5BY, UK
Tel: 08703 330070 Fax: (01525) 718988 e-mail: mail@weberbuildingsolutions.co.uk

To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application, and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that he has consulted our latest literature.